



## Ancillary Equipment

**Van Tuyl over the years has developed and manufactured equipment for the ceramic industry.**

**Extruder** - hand operated extruder for producing small shapes, such as cup handles and edging strips. The unit can be bench or wall mounted and is supplied with three pre-cut dies and two blanks.

**Pug Mills** – our Pug Mill is designed around a 170mm diameter full auger turning at 38 r.p.m. that reduces the clay to an outlet diameter of 50mm, 75mm or 100mm dependent on a client's requirements.

**Slab Roller** - Slab Roller uses the “moving table” principle as opposed to the “moving roller” assembly. We manufacture a free-standing unit with table sizes of 800mm by 600mm and a smaller bench unit of 600mm by 450mm.

**Blunger** - used by Potters who “cast” items such as plates, mugs and figurines using “slip” and “moulds”. The Blunger has a 0.37 Kw motor driving through a 10:1 reduction gearbox to keep the slip in suspension.



Clay Slab Roller Kiln



Pug Mill



Blunger Kiln



Clay Mixer

### Other Pottery & Ceramic Equipment

Product Code #	Description	Detail
VTPG01	Pug Mill	Input Diameter 200mm, Output Diameter 50mm to 100mm, Output speed 35rpm.
VTCM01	Clay Mixer	Motor 2.2kW 1440rpm, Rotation speed - 56rpm, Size (1600mm (L) x 850mm (H) x 500mm (W).
VTBL200	Blunger	200lt Tank, Output 50mm Diameter, Rotation speed - 145rpm, Size (1800mm (H) x 600mm (D) x 600mm (W).
VTSR-450	Slab Roller	Slab Roller ( Table Top ), table size 450mm x 600mm
VTSR-650	Slab Roller	Slab Roller ( Free Standing ), table size 650mm x 800mm

**We also supply other kiln parts like - Kiln Bung (various diameters) / Replacement Door Seal Kit / Replacement Controllers / Energy Regulators / Ceramic Fibre Board / Insulating Kiln Brick / Replacement Door Latch.**

**Postal Address : P.O. Box 166889, Brackendowns, 1454,  
Street Address: 28 Van der Bijl St, Alrode South, Johannesburg  
Tel: 011-868-1387/9**

**Email: [sales@vantuyl.co.za](mailto:sales@vantuyl.co.za)**

**Website: [www.vantuyl.co.za](http://www.vantuyl.co.za)**